



Commercial & industrial lighting

MS Floodlight

Code

LPFL-50MS01



Key specifications

Power	50 W
Luminous flux	4,980 to 5,120 lm
Colour temperature	2700 K, 4000 K, 6500 K
IP rating	IP66
Efficacy	100 lm/W

Technical specifications

Electrical	
Dimmable	No
Photometric	
Lifetime	50,000 h
Mechanical	
IK rating	IK08
Dimensions	295X70X138mm

Downloads

Datasheet (LPFL-50M01.pdf)

<https://www.liperlighting.com/uploads/LPFL-50M01.pdf>

Datasheet (LPFL-100M01.pdf)

<https://www.liperlighting.com/uploads/LPFL-100M01.pdf>

Datasheet (LPFL-150M01.pdf)

<https://www.liperlighting.com/uploads/LPFL-150M01.pdf>

Specifications as published by the brand.

Generated on 25 October 2026

Product page: <https://liperalbania.com/en/product/ms-floodlight?v=lpfl-50ms01>

MS Floodlight · LPFL-50MS01

Datasheet (LPFL-200M01.pdf)

<https://www.liperlighting.com/uploads/LPFL-200M01.pdf>

Datasheet (LPFL-300M01.pdf)

<https://www.liperlighting.com/uploads/LPFL-300M01.pdf>

Datasheet (LPFL-400M01.pdf)

<https://www.liperlighting.com/uploads/LPFL-400M01.pdf>

Datasheet (LPFL-500M01.pdf)

<https://www.liperlighting.com/uploads/LPFL-500M01.pdf>

Datasheet (LPFL-600M01.pdf)

<https://www.liperlighting.com/uploads/LPFL-600M01.pdf>

Datasheet (Liper-IP66-MS-LED-flood-light-DOB.pdf)

<https://www.liperlighting.com/uploads/Liper-IP66-MS-LED-flood-light-DOB.pdf>
